

YOUNGMAN®

TRADE APPROVED SINCE 1926

Double-Section

Sliding Roof Ladder

150kg

LOAD CAPACITY
(Load includes user, tools,
materials, etc)



Safety Tested

Designed to be a longer and more compact product that is lighter to maximise manoeuvrability and storage without losing any strength.

Suitable for roof slopes of between 15° and 55°



Visit us online to see our full range of products youngmanaccess.com

Double-Section Sliding Roof Ladder



Safety Tested

Designed to be a longer and more compact product that is lighter to maximise manoeuvrability and storage without losing any strength.

Suitable for roof slopes of between 15° and 55°

Heavy-duty roof hook with large non-slip rubber end bar for a superior apex fit

Large wheels with low rolling resistance

Optimum weight frame for ease of positioning

Heavy-duty locking catches and non-slip rubber-sleeved support bars for roof protection

SPECIFICATIONS

Product Code	Rungs Per Section (m)	Closed Height (m)	Open Height (m)	Weight (kg)
57663000	8 x 10	3.20	4.89	13.05
57663600	10 x 12	3.77	6.00	14.77
57664000	12 x 14	4.33	7.13	16.80
57664600	14 x 16	4.89	8.25	18.53

* Maximum Safe Working Height based on 1.75m (5'9") as the average reach height of a person